



Model		XVR7104-GL
System	Main processor	Industrial-grade embedded HiSilicon CPU
	Operating system	embedded Linux
	System resources	Simultaneously multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	support 16-bit true color graphical menu interface and mouse operation
	Preview	1/4 split screen
Video	Codec	H.265 (High Profile)
	Monitor quality	VGA ; HDMI : HD
	Playback quality	AHD、TVI、CVR、CVBS-3M~5MP
	Encode ability	4*AHD、TVI、CVR、CVBS-3M~5MP
	Decode ability	4*AHD、TVI、CVR、CVBS-3M~5MP
	Multi-mode input	analog : 4*AHD、TVI、CVR、CVBS~3M~5MP
		hybrid : 2*AHD、TVI、CVR、CVBS-3M~5MP (analog) +2*1080P(network)
	Network only : 4*5MP	
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local	
Audio	G.711A	
Intercom	support	
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	1*5MP
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	4ch BNC
	Video output	1ch VGA, 1ch HDMI
	Audio input	1CH RCA
	Audio output	1CH RCA
	Alarm input	0(Can be extended to 4ch)
	Alarm output	0(Can be extended to 1ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 6TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/3A
	Power Consumption	<15W (without HDD)
	Temperature	0°C—+55°C
	Humidity	10%—90%
	Working environment	86kpa—106kpa
	Dimension	255*230*45mm
	Weight	2KG